



MEAT GRINDER

Powerful grinder system with 4 different output diameter. Range include 160mm; 200mm; 250mm and 300mm. Solid Hygiene stainless steel made. Variable speed driver supply. Wide speed adjustment and soft-start function. High torque Oil cooling gearbox. CE standard approved.

FEATURE

| | | | | |
|-----------------------------|------------------|------------------|------------------|------------------|
| Model | C160G - B | C200G - B | C250G - B | C300G - B |
| Power | 18.5 Kws | 30 Kws | 37 Kws | 55 Kws |
| Output Φ | 160 mm | 200 mm | 250 mm | 300 mm |
| Max. Dimension Frozen Block | 50x50x100mm | 100x100x150mm | 200x200x150mm | 600x400x200mm |
| Dimension | 1450x1000x1400mm | 1700x1150x1570mm | 2000x1200x1700mm | 2300x1300x1850mm |
| Capacity | 1 - 2 T / Hour | 1.5 - 3 T / Hour | 2 - 5 T / Hour | 2 - 6 T / Hour |
| Weight | 850 Kgs | 950 Kgs | 1,550 Kgs | 1,800 Kgs |

OPTIONAL

200L Bin Lifter / Buggy Dumper
Food Grade Conveyor System
Hydraulic Lifting System (For C250 Only)





MIXER GRINDER

Powerful grinder system with 4 different output Diameter. Range include 160mm; 200mm; 250mm And 300mm. Solid hygiene stainless steel made. Variable speed driver supply wide speed Adjustment and soft-start function. High torque Oil cooling gearbox. CE standard approved.

FEATURE

| | | | | |
|-----------|------------------|-------------------|-------------------|-------------------|
| Model | G130/140L | G160/300L | G200/600L | G250/1200L |
| Power | 8.6 Kws | 21.5 Kws | 28 Kws | 41 Kws |
| Output Φ | 130 mm | 160 mm | 200 mm | 250 mm |
| Hopper | 140 L (100 Kgs) | 300 L (250 Kgs) | 600L (450 Kgs) | 1200 L (980 Kgs) |
| Dimension | 1200x1100x1000mm | 1910x1190x1650mm | 2300x1500x1800mm | 2530x1600x2000mm |
| Capacity | up to 4 T / Hour | up to 10 T / Hour | up to 16 T / Hour | up to 18 T / Hour |
| Weight | 550 Kgs | 950 Kgs | 1,550 Kgs | 1,800 Kgs |

OPTIONAL

200L Bin Lifter / Buggy Dumper
Food Grade Conveyor System
Hydraulic Lifting System (For G200 Only)



BOWL CUTTER

High performance bowl chopper/cutter
Made with hygiene stainless steel 304,
Variable speed control for knife with
Bowl, Stable hydraulic system for loading
And unloading process. Smart PLC and color HMI system. Fine emulsifying with low
Noise. CE standard approved.



FEATURE

| | | | |
|-------------|--------------------------------|------------------|------------------|
| Model | K130L | K200L | K330L |
| Power | 33.7 Kws | 62.4 Kws | 82.4 Kws |
| Bowl | 130 L (100 Kgs) | 200L (160 Kgs) | 330L (270 Kgs) |
| Knife Speed | 150 - 3800 rpm (Max. 4200 rpm) | | |
| Bowl Speed | 4 - 17 rpm (Max. 20 rpm) | | |
| Dimension | 1900x1300x1500mm | 2750x2000x1750mm | 2900x2150x1850mm |
| Weight | 1,500 Kgs | 3,500 Kgs | 4,000 Kgs |



HIGHLIGHT

Solid stainless steel made
High speed emulsifying
Low noise and maintenance frequency
High safety quality

MIXER

Fine mixing processing equipment with variable Speed driver. Smart PLC and colour HMI control. Optional vacuum system and hydraulic lifting system For M600L. CE standard approved.



FEATURE

| | | | |
|--|------------------|------------------|------------------|
| Model | M300L | M600L | M1200L |
| Power | 3 Kws | 6 Kws | 11 Kws |
| Hopper | 300 L (250 Kgs) | 600L (450 Kgs) | 1200L (1000 Kgs) |
| Mixing Speed | Variable Speed | | |
| Dimension | 1910x1190x1650mm | 2350x1500x1800mm | 2530x1600x2000mm |
| Weight | 700 Kgs | 950 Kgs | 1,300 Kgs |
| Optional Vacuum System / Hydraulic Lifting System (M600L Only) | | | |



BIN LIFTER

High torque screw driver lifter for different height demands..
2.2 Kws electromagnetic braker safety motor.
4mm stainless steel 304 made.Optional mobile cart.
CE standard approved.